

DECLARATION OF PERFORMANCE

14TG/BL-Z/2/13

1. Unique identification code of the product type:

ZEFIR Steel Roof Sheet

2. Number of type, batch or lot or any other element to identify the construction product required according to art.11 law 4:

See the technical specification of the product.

3. Provided by the manufacturer intended use or uses of a construction product in accordance with applicable harmonized technical specification

Self-supporting profiled sheets applied in building industry to make roof covers and wall cladding of the buildings

4. Name, registered trade mark or registered trade name and contact address details required according to art.11 law 5:

BUDMAT
Bogdan Więcek, Otolińska 25
09-407 Płock

5. System or systems of assessment and verification of constancy of construction product functional properties determined in annex V:

Assessment system 3 and 4

6. In case of declaration of functional properties concerning construction product covered by harmonized standard:

Polish Standard PN-EN 14782:2008 - Self supporting metal sheets for roofs, outdoor and indoor cladding. Characteristics and requirements of the product.

Usage and range of construction product usage: in buildings located in the areas of the following corrosion categories (according to: PN EN ISO 12944-2:2001):

- sheets with zinc coating of 275g/m² or aluminium-zinc alloy (AZ 150) of 150g/m² covered with polyester organic coatings of thicknesses 25µm, 30µm or SP NOVA 50 or HDX 55 µm, PVDF (25µm) - in the areas of corrosion category C1, C2, C3

- sheets with coating Z 350 or AZ 185g/m² – applicable outdoor in the areas of corrosion category C1, C2, C3

Lp.	Technical characteristics	Declared value	
1	Fire resistance	class B ROOF (t1), class B ROOF(t2), class B ROOF (t3)	
2	Reaction to fire	Coating thickness ≤25µm	Coating thickness >25µm
		A1	A2-s2,d0

Concentrated load resistance 1,2KN



Type of profiling sheet	Thickness [mm]	Span [mm]
Steel roofing sheet ZEFIR	0,50	350 – 400

Water resistance, permeability of water, air and vapor – Products that don't have perforations (as damages) are waterproof and impermeable to steam and air.

Change of dimensions – thermal expansion should be taken into account where such change may affect the use of product, correspondent steel thermal expansion coefficient $12 \times 10^{-6} \text{ K}^{-1}$ should be taken into account.

Building Research Institute:

Department of Durability and Protection of Building carried out researches of products corrosion resistance and issued an opinion NO-2/819/A/2008

Fire Research Department NP-1259.2.1/07/AK; NP-1259.2.2/07/AK; NP-1259.2.3/07/AK, NP-1259.2.3/2007/AK

Department of Durability and Protection of Building carried out researches of products corrosion resistance and issued an opinion NO-2/819/A/2008 and research report Nr LM00-0785/11/Z00NM – assessment system 4

Fire Research Department carried out researches of painted coatings fire resistance and issued an opinion NP-1259.2.1/07/AK; NP-1259.2.2/07/AK; NP-1259.2.3/07/AK, NP-1259.2.3/2007/AK – assessment system 3

Water resistance, permeability of water, air and vapor – Products that don't have perforations (as damages) are waterproof and impermeable to steam and air.

Change of dimensions – thermal expansion should be taken into account where such change may affect the use of product, correspondent steel thermal expansion coefficient $12 \times 10^{-6} \text{ K}^{-1}$ should be taken into account.

Dimension tolerances for roof products are described in standard PN-EN 508-1

7. Product functional properties defined in paragraph 3 are consistent with those declared in paragraph 6

This declaration of performance is issued under the sole responsibility of the manufacturer. On behalf of manufacturer signed:

On behalf of manufacturer signed
Production Director Mieczysław Kijek
(name and position)

Płock 01.07.2013



.....Mieczysław Kijek.....
Podpis osoby upoważnionej



DECLARATION OF PERFORMANCE

14TG/BL-Z/2/13

- 1. Unique identification code of the product type:**
ZEFIR Steel Roof Sheet
- 2. Number of type, batch or lot or any other element to identify the construction product required according to art.11 law 4:**
See the technical specification of the product.
- 3. Provided by the manufacturer intended use or uses of a construction product in accordance with applicable harmonized technical specification**
Self-supporting profiled sheets applied in building industry to make roof covers and wall cladding of the buildings
- 4. Name, registered trade mark or registered trade name and contact address details required according to art.11 law 5:**
BUDMAT
Bogdan Więcek, Otolińska 25
09-407 Płock
- 5. System or systems of assessment and verification of constancy of construction product functional properties determined in annex V:**
Assessment system 3 and 4
- 6. In case of declaration of functional properties concerning construction product covered by harmonized standard:**

Polish Standard PN-EN 14782:2008 - Self supporting metal sheets for roofs, outdoor and indoor cladding. Characteristics and requirements of the product.

Usage and range of construction product usage: in buildings located in the areas of the following corrosion categories (according to: PN EN ISO 12944-2:2001):

- sheets with zinc coating of 275g/m² or aluminium-zinc alloy (AZ 150) of 150g/m² covered with polyester organic coatings of thicknesses 25µm, 30µm or SP NOVA 50 or HDX 55 µm, PVDF (25µm) - in the areas of corrosion category C1, C2, C3

- sheets with coating Z 350 or AZ 185g/m² – applicable outdoor in the areas of corrosion category C1, C2, C3

Lp.	Technical characteristics	Declared value	
1	Fire resistance	class B ROOF (t1), class B ROOF(t2), class B ROOF (t3)	
2	Reaction to fire	Coating thickness ≤25µm	Coating thickness >25µm
		A1	A2-s2,d0

Concentrated load resistance 1,2KN

Type of profiling sheet	Thickness [mm]	Span [mm]
Steel roofing sheet ZEFIR	0,50	350 – 400

Water resistance, permeability of water, air and vapor – Products that don't have perforations (as damages) are waterproof and impermeable to steam and air.

Change of dimensions – thermal expansion should be taken into account where such change may affect the use of product, correspondent steel thermal expansion coefficient $12 \times 10^{-6} \text{ K}^{-1}$ should be taken into account.

Building Research Institute:

Department of Durability and Protection of Building carried out researches of products corrosion resistance and issued an opinion NO-2/819/A/2008

Fire Research Department NP-1259.2.1/07/AK; NP-1259.2.2/07/AK; NP-1259.2.3/07/AK, NP-1259.2.3/2007/AK

Department of Durability and Protection of Building carried out researches of products corrosion resistance and issued an opinion NO-2/819/A/2008 and research report Nr LM00-0785/11/Z00NM – assessment system 4

Fire Research Department carried out researches of painted coatings fire resistance and issued an opinion NP-1259.2.1/07/AK; NP-1259.2.2/07/AK; NP-1259.2.3/07/AK, NP-1259.2.3/2007/AK – assessment system 3

Water resistance, permeability of water, air and vapor – Products that don't have perforations (as damages) are waterproof and impermeable to steam and air.

Change of dimensions – thermal expansion should be taken into account where such change may affect the use of product, correspondent steel thermal expansion coefficient $12 \times 10^{-6} \text{ K}^{-1}$ should be taken into account.

Dimension tolerances for roof products are described in standard PN-EN 508-1

7. Product functional properties defined in paragraph 3 are consistent with those declared in paragraph 6

This declaration of performance is issued under the sole responsibility of the manufacturer. On behalf of manufacturer signed:

On behalf of manufacturer signed
Production Director Mieczysław Kijek
(name and position)

Płock 01.07.2013

BUDMAT
..... Mieczysław Kijek
Podpis osoby upoważnionej