

STORAGE AND TRANSPORT: PROAQUA GUTTER SYSTEM

The gutters and downpipes of the ProAqua system must be stored and transported on a flat surface in a horizontal position. It is permitted to store the products on stands and metal racks. In order to avoid mechanical damage, the sharp edges of the steel profiles in contact with the gutters and downpipes must be carefully protected in storage and during transport. The first layer of gutters and pipes should always, lie on level sleepers and be in contact with them along their entire length. The permitted storage height is 1 metre.

ProAqua system gutters and downpipes are packed in plastic sleeves to protect them from dust, rain and excessive sunlight. Do not store pipes and gutters without protective film outside the warehouse, exposed directly to sunlight.

Fittings packed in cardboard boxes should be stored and transported under cover. The load must be immobilised during transport. It is recommended that loading and unloading (individual packages) should be carried out manually with due care (do not throw the cardboard boxes) and when using mechanical equipment, do not allow localized crushing of the elements or packages. Most fittings are packed in individual plastic bags. Do not expose fittings packed in this way to prolonged and direct sunlight.

STORAGE AND TRANSPORT: SOFFIT

To avoid possible deformation of the products, all elements should be stored and transported flat, under cover, supported along the entire length. The height of storage should not exceed 1 metre.

The temperature in rooms where BUDMAT roof soffit system elements are stored should not exceed 50°C. During transport, the load should be properly immobilised and secured. Do not allow localized crushing of collective packaging, as it may cause mechanical damage to the elements.

BUDMAT® Bogdan Więcek

NIP 774 001 50 83

ul. Otolińska 25
09-407 Płock
www.budmat.plBank Zachodni WBK S.A.
PL43 1500 1618 1216 1000 5646 0000CITIBANK HANDLOWY S.A.
PL93 1030 1234 0000 0000 0856 7000**Dachy i Elewacje**

T: +48 24 268 02 79

Profile

T: +48 24 268 93 19

Stalowe Centrum Serwisowe

T: +48 24 268 31 99

Stalowy System Rynnowy

T: +48 23 672 22 38

System Rynnowy PVC

T: +48 24 268 02 65

Podmioty Grupy BUDMAT:

BUDMAT® Transport Sp. z o. o.09-407 Płock
ul. Otolińska 25
T: +48 24 268 03 71
www.budmattransport.pl**BUDMAT® Materiały Budowlane Sp. z o. o.**09-407 Płock
ul. Otolińska 25
T: +48 502 197 197